Harlequin Clarity

Harlequin Clarity is a durable transparent vinyl performance floor with a slip-resistant embossed surface. It is ideal for reverse digital printing, where the printed design is on the underside of the floor and therefore protected from wear and damage.

Installation: Harlequin Clarity is specified for permanent or temporary installation. For permanent installation the joins are cold welded and for temporary installation double sided tape is used to form a continuous performance surface.

Usage: When reverse printed, Harlequin Clarity is suitable for high-traffic commercial use and as a dance surface. It can also be used as a clear protective wear layer which allows the floor underneath to show through or it can be used to protect an existing floor, such as a floor in a listed building.

Specification Guide

| opoomounon outdo | |
|-------------------------------|---|
| Material | Homogeneous vinyl |
| Permanent or Portable | Both |
| Roll Length | 15m |
| Roll Width | 1.52m |
| Maximum Printed Area | 1.47m x 14.24m |
| Thickness | 1.90mm |
| Weight | 2.47kg/m ² |
| Finish | Embossed |
| Fire Rating | Cfl-s1 (EN 13501-1) |
| Warranty - Unprinted Flooring | 10 years if installed by Harlequin |
| | 5 years if installed by the customer |
| Warranty - Printed Flooring | The warranty period will depend upon the intended use. |
| Fixing Type | Adhesive or Tape |
| Seams | Cold Welded or Taped |
| Gloss Level | Nominal 6 |
| Lightfastness | ≥6 |
| VOC Emissions | ≤0.5mg/m³ |
| Recyclability | 100% |
| Underfloor Heating | Suitable for use with underfloor heating |
| Third Party Certification | Environmental Product Declaration A ⁺ LEED, BREEAM, REACH Compliant |



Available Colours:

000 - Clear



Homogeneous vinyl with support and a slip-resistant dance surface





