


Harlequin Showfloor™



Harlequin Showfloor is a multi-layered vinyl performance floor with a cellular foam backing and an embossed display surface to help prevent scuff marks. It is lightweight, reusable, and perfect for use as a temporary floor at any event.

Installation: Harlequin Showfloor is specified for temporary 'loose-lay' installation. The joins are taped to form a continuous performance surface. It can be rolled out on any flat, smooth surface.


Usage: Ideal for fashion shows, exhibition stands, stage sets, museums, events and art displays.

Specification Guide

Material	Heterogeneous vinyl
Permanent or Portable	Portable
Roll Lengths	20m, 30m
Roll Width	2m
Thickness	2.6mm
Weight	1.7kg/m ²
Finish	Embossed
Fire Rating	Bfl-s1 (EN 13501-1)
Warranty	2 years
Fixing Type	Tape
Seams	Taped
Light Reflectance	021-2, 034-48, 043-10, 019-84
VOC Emissions	≤0.5mg/m ³
Underfloor Heating	Suitable for use with underfloor heating

Available Colours:

Black - 021



White - 019



Grey - 034



Red - 043



HARLEQUIN
www.harlequinfloors.com



Shakespear's Globe



Who performs
on Harlequin
Showfloor™



GUBA™
GROW UNITE BUILD AFRICA



Ballet Arizona

BALLET
ARIZONA
IB ANDERSEN ARTISTIC DIRECTOR

ACP



Capital Summertime Ball



HARLEQUIN
www.harlequinfloors.com

If you would like further information or advice please contact us on
+91 99300 12997 or india@harlequinfloors.com

The Company reserves the right to make any variation in design or construction of the material described. Harlequin® is a registered trademark of British Harlequin plc. © Harlequin Floors 07/2023